




Fjederpakke VT4625-B


Forkomprimerede fjederkasser bruges primært til vibrationsisolering af tunge maskinfundamenter og bygninger. VT4625-serien bruges, hvor kravet til resonansfrekvens er ca. 3,5 Hz.

Fjederpakke 4625-B4

Tekniske specifikationer



VT4625-BAXYP
VT46 = series
25 = max. deflection
BA = box type (2, 4, 6 or 9 springs)
X = number of OUTER springs
Y = number of INNER springs
P = Pre compressed





VT4625-B4 tekniske specifikationer

spring-package-vt4625-b4-technical-specifications.xlsx

Dimensioner og belastningsområde

Ref.	L	B	A	Belastningsområde
	(mm)	(mm)	(mm)	(kN)
VT4625-B2	190	360	250	120 - 212
VT4625-B4	360	360	250	200 - 420
VT4625-B6	530	360	250	325 - 635
VT4625-B9	530	530	250	525 - 950

Downloads



vt4625-b



Kontaktoplysninger

Sverige

+46 176207880
info@vibratec.se

Norge

+47 33070750
info@vibratec.no

Danmark

+45 49132244
info@vibratec.dk

Estland

+372 56627990
info@vibratec.ee

Finland

+35 8402589117
palvelu@3di.fi

Indien

+91 7755996308
rc@vibratec.in



vibratec.org/linkedin



vibratec.org/youtube



vibratec.org/vimeo