



Impact mat Comfort 5

This thin 5 mm impact sound insulating material is ideal for applications with limited installation heights. REGUPOL comfort 5 is a 5 mm thin impact sound insulation layer for use under floating floors and screeds. Due to its very low construction height, it is frequently used in projects with major construction height limitations.

Product Characteristics

Impact sound insulating underlayment for various floor structures under screed beds and floating floors with a maximum live load $\leq 5 \text{ kN/m}^2$, CE certified as per European Technical Assessment.

Material

PUR-bonded elastomers

Weight

2.2 kg/m^2

Dimensions

Length: 2,250 mm, Width: 1,150 mm, Thickness: 5 mm

Product Applications

Used for impact sound insulating layer under screed beds and floating floors for both residential and commercial use, live load $\leq 5 \text{ kN/m}^2$, e. g. floor renovations, new buildings, reconstructions of apartments, commercial buildings or hotels.

Downloads



REGUPOL comfort
5 | Technical data



REGUPOL comfort |
Declaration of
Performance



REGUPOL comfort
5 | Under cement
screed test report –
english



REGUPOL comfort |
installation
guideline



EPD –
Environmental
Product Declaration
– Regupol



REGUPOL Cradle to
Cradle Certificate

Contact information

Sweden	Norway	Denmark	Estonia	Finland	India
+46 176207880 info@vibratec.se	+47 33070750 info@vibratec.no	+45 49132244 info@vibratec.dk	+372 56627990 info@vibratec.ee	+35 8402589117 palvelu@3di.fi	+91 7755996308 rc@vibratec.in
	 vibratec.org/linkedin	 vibratec.org/youtube	 vibratec.org/vimeo		