



Spring Isolator VT4090

A very soft isolator with integrated adjustable movement limiters. It has a very low natural frequency of 3.5 – 5 Hz Designed especially for suspension of mobile equipment. Vibration isolation and suspension of propulsion engines, generating sets, compressors, deck houses etc.

Product Characteristics

A very soft isolator with integrated adjustable movement limiters. Designed especially for suspension of mobile equipment. Designed with resilient elements:

- Spring in high tensile steel
- cushions in 18/8 stainless steel
- Housing in zinc plated steel

Natural frequency: 3.5 – 5 Hz

Mechanical strength: 5 g

Temperature range: -90°C – +300°C

Product Applications

Vibration isolation and suspension of:

- propulsion engines
- generating sets
- compressors
- deck houses
- and more...


Notes

The built in movement limiters must be adjusted when the suspended equipment has its working condition. The adjustment is done by turning the uplift limiter with a wrench.

The isolator can be delivered pre-compressed.

Type Approved by DNV-GL.

Technical Specifications



 Spring-isolator-VT4090-technical specifications

spring-isolator-vt4090-technical-specifications.xlsx

Load Ranges

Ref	Static load in daN (≈kg)	
VT4090-Y3-I	5700	9500
VT4090-Y3	4700	7800
VT4090-Y2-I	3500	5800
VT4090-Y2	2500	4100
VT4090-Y1-I	2100	3800
VT4090-Y1	1300	2100
I	900	1600



Contact information

Sweden	Norway	Denmark	Estonia	Finland	India
+46 176207880 info@vibratec.se	+47 33070750 info@vibratec.no	+45 49132244 info@vibratec.dk	+372 56627990 info@vibratec.ee	+35 8402589117 palvelu@3di.fi	+91 7755996308 rc@vibratec.in

 vibratec.org/linkedin

 vibratec.org/youtube

 vibratec.org/vimeo