



Spring Hanger VT4524-2X

All-metal hanger, perfect for isolation of pipes, stabilisation of frames and equipment. Mounts with very low natural frequency and accepts both static and dynamic tension forces. This mount has two springs made of high tensile steel and resilient cushions in stainless steel wire. Scrolls in aluminium. Other parts in mild steel.

Product Characteristics

Natural frequency: 3-4 Hz, depending on preload.

Maximum excitation: ± 1 mm

Mechanical strength: 2 g

Amplification factor: < 8

Temperature range: -90°C to $+300^{\circ}\text{C}$



Product Applications

Perfect for isolation of exhaust-, air- and steam-pipes. Stabilisation of frames, heavy ceilings and equipment on vessels, vehicles etc.

For smaller loads, see isolator [VT4524-0X](#)

For larger loads, see isolator [VT4524-4X](#).

Technical Specifications



 Spring-isolator-VT4524-2X-technical specifications

spring-isolator-vt4524-2x-technical-specifications.xlsx

Load - Dimensions - Weight

Ref	Load range in daN (≈kg)	A	B	Weight (kg)
VT4524-25	420 - 620	100	120	10.5
VT4524-26	600 - 840	100	120	10.6
VT4524-27	700 - 1100	100	120	10.7



Contact information

Sweden	Norway	Denmark	Estonia	Finland	India
+46 176207880 info@vibratec.se	+47 33070750 info@vibratec.no	+45 49132244 info@vibratec.dk	+372 56627990 info@vibratec.ee	+35 8402589117 palvelu@3di.fi	+91 7755996308 rc@vibratec.in

 vibratec.org/linkedin

 vibratec.org/youtube

 vibratec.org/vimeo